

2640M-24V88

1 1/2" - 10,000 PSI GOLDEN EAGLE



Chemical applications

#									Test pressure			Collapse pressure	Max length
	mm	inch	mm	inch	bar	psi	bar	psi					
2640M-24V88	38.0	1 1/2	70.5	2.78	690	10,000	2300	33,350	1035	500.0	7.20	65	600

APPLICATIONS

Suitable for use in cementing, acidizing and water / chemical injection applications. Increased chemical resistance and temperature rating when compared to standard Black Eagle.

FEATURES

- Short term use to +100°C
- Suitable for use with aggressive chemicals such as hydrochloric acid
- ColorGard, visual early warning system
- Long continuous lengths available
- Fluoropolymer based

CONSTRUCTION

Core tube: Fluoropolymer based inner core.
Pressure reinforcement: 4 layers of high tensile steel wire.
Cover: Extra thick dual layer TPU sheath.
Colour: ColorGard™ – red inner sheath and golden outer sheath.


TEMPERATURE RANGE

-40°C up to +70°C / -40°F up to 158°F.

FITTINGS


NPT Male fitting

#		A	B	ØR	
		mm	mm	mm	bar
6015X-32-24-TC	2 NPT	231.0	107.0	85.0	690




Metric swivel fitting with O-ring

#		A	B	H	
		mm	mm	mm	bar
1C95X-38-24COSK-TC	M52 x 2	143.0	50.0	65.0	1035




1502 Hammerlug union female

#		A	B	
		mm	mm	bar
1HN5X-32-24C4462-TC	4 1/8 - 3 ACME	245.1	108.0	1035



1502 Hammerlug union male

#		A	B	
		mm	mm	bar
1HE5X-32-24C4462-FLATTC	4 1/8 - 3 ACME	232.0	108.0	1035



Please Note: Variety of fittings in mild steel or stainless steel available, other fittings available on request. We reserve the right to make technical changes without notice.