







ROUGH NECK HIGH PRESSURE SLIM HOLE ROTARY



Hose applications

#								
	inch	inch	bar	psi	bar	psi	inch	lbs / per ft
SHR3K-48	3	3.61	207	3,000	500	7,250	33.10	5.38
SHR3K-64	4	5.22	207	3,000	500	7,500	54.75	13.65

APPLICATIONS

High pressure transfer hose - 3,000 psi 3" and 4" high pressure transfer hose that is flexible, has a small diameter, and is easier to handle than similar hoses. It is extremely an flexible and durable hose.

FEATURES

- Large bore high flow hoses with high pressure capabilities.
- Customised assemblies offering either NPT male pipe or FIG1502 integral hose tails.
- Rough Neck high pressure transfer hose is a 2,900 psi 3" high pressure transfer hose that is flexible, easier to handle than hoses similar to it and has a small diameter.

CONSTRUCTION

Core tube: Black, NBR for oil and liquid mud resistant.
Pressure reinforcement: Multiple high tensile steel wire spiral layers and braided layer.
Outer cover: Black oil and abrasion resistant NBR cover with Green Mylar lay line.

TEMPERATURE RANGE

-4°F to 212°F (max 248°F).

Please Note: We reserve the right to make technical changes without notice.