



# 2640N-24V80-15K

## 1 1/2" - 15,000 PSI BLACK EAGLE

### Offshore applications

#									Test pressure 			Collapse pressure	Max length
	mm	inch	mm	inch	bar	psi	bar	psi					
2640N-24V80-15K	38.0	1 1/2	66.0	2.60	1035	15,000	2330	33,750	1553	500.0	6.5	66	1,500

### APPLICATIONS

Designed for use in acidising, cementing, methanol injection, well stimulation and control fluids. Used as an alternative to steel pipe, flexible pipe and rubber hose. Can be utilised onshore or offshore.

### FEATURES

- ColorGard, visual early warning system
- Nylon 11 core tube offers high cleanliness
- Available in long continuous lengths
- Smaller OD than flexible pipe allows more hose per reel
- Excellent chemical resistance providing long service life
- Lightweight when compared to competing products
- More efficient deployment and recovery

### CONSTRUCTION

**Core tube:** PA11, methanol washed.  
**Pressure reinforcement:** 6 layers of high tensile steel wire.  
**Cover:** Extra thick dual layer TPU sheath.  
**Colour:** ColorGard™ – red inner sheath and black outer sheath.


### TEMPERATURE RANGE

-40°C up to +70°C / -40°F up to 158°F.

### FITTINGS


#### Metric swivel fitting with O-ring

#		A	B		
		mm	mm	mm	bar
1C95X-38-24C0SK-KOP2	M52 x 2	143.0	50.0	65.0	1035




#### 1502 Hammerlug union female: Special steel and stainless steel materials.

#		A	B	
		mm	mm	bar
1HN5X-32-24C4462-KOP2	4 1/8 - 3 ACME	245.1	108.0	1035



#### 1502 Hammerlug union male: Special steel and stainless steel materials.

#		A	B	
		mm	mm	bar
1HE5X-32-24C4462-KOP2	4 1/8 - 3 ACME	232.0	108.0	1035



**Please Note:** Variety of fittings in mild steel or stainless steel available, other fittings available on request. We reserve the right to make technical changes without notice.