



2640N-48V80

3" - 15,000 PSI BLACK EAGLE

Offshore applications

#									Test pressure			Collapse pressure	Max length
	mm	inch	mm	inch	bar	psi	bar	psi					
2640N-48V80	75.0	3	130.0	5.12	1035	15,000	2330	33,750	1553	1200.0	27.50	80	250

APPLICATIONS

Designed for use in acidising, cementing, methanol injection, well stimulation and control fluids. Used as an alternative to steel pipe, flexible pipe and rubber hose. Can be utilised onshore or offshore.

FEATURES

- ColorGard, visual early warning system
- Nylon 11 core tube offers high cleanliness
- Available in long continuous lengths
- Smaller OD than flexible pipe allows more hose per reel
- Excellent chemical resistance providing long service life
- Lightweight when compared to competing products
- More efficient deployment and recovery
- DNV Type approval (API 7K and API 17J)

CONSTRUCTION

Core tube: PA11, methanol washed.
Pressure reinforcement: 6 layers of high tensile steel wire.
Cover: Extra thick dual layer TPU sheath.
Colour: ColorGard™ – red inner sheath and black outer sheath.


TEMPERATURE RANGE

-40°C up to +70°C / -40°F up to 158°F.

FITTINGS


1502 Hammerlug union female

#		A	B	
		mm	mm	bar
1HN5X-48-48	5 3/8 - 3 1/2 ACME	405.0	194.0	1035



1502 Hammerlug union male

#		A	B	
		mm	mm	bar
1HE5X-48-48-FLAT	5 3/8 - 3 1/2 ACME	395.0	184.0	1035



Please Note: Variety of fittings in mild steel or stainless steel available, other fittings available on request. We reserve the right to make technical changes without notice.