







# A-JET RUBBER / JW-BLUE

## RUBBER DRAIN / SEWER CLEANING HOSE



### Drain / sewer cleaning applications

#										
	mm	inch	mm	bar	psi	bar	psi	mm	kg/m	
AJ320-08	12.7	1/2	19.2	320	4,640	800	11,600	80.0	0.34	
AJ440-08	12.7	1/2	22.2	440	6,380	1100	15,950	178.0	0.65	
JW-8-BLUE	12.7	1/2	20.7	400	5,800	1600	23,200	130.0	0.58	

### APPLICATIONS

Medium to high pressure water jetting applications to include drain, sewer and stack pipe cleaning / unblocking, the JW version is also excellent for the higher temperature requirements with a range of up to +150°C.

### FEATURES

- High abrasion resistance
- High ozone and weather resistance
- Flame resistance to a wide range as specifications
- Applicable specifications: EN 853 1SNK - EN 853 2SN - SAE R100 R2AT - BS EN1829-2

### CONSTRUCTION

**Core tube:** Synthetic rubber.  
**Pressure reinforcement:** One or two high tensile steel wire braids.  
**Cover:** AJ320 & AJ440: Synthetic rubber, MSHA flame retardant approved.  
 JW: Synthetic rubber smooth finish, pin pricked.  
**Colour:** AJ320 & AJ440: Black. JW: Blue.

### TEMPERATURE RANGE

**Water**  
 AJ320 & AJ440: -40°C up to +85°C.  
 JW: -40°C up to +150°C.



**Please Note:** Variety of fittings in mild steel or stainless steel available, other fittings available on request. We reserve the right to make technical changes without notice.