

UHP TRIPLE PUMP TEST RIG TESTING UP TO 80,000 PSI

AB-T-UHP3 - 600 / 6000 / 8000



Alternative tank option



Technical data

	UHP Triple pump test rig
Test pressure	600 - 80,000 psi (41 - 5,516 bar)
Drive	Manual control
Flow	13 LPM @ 0 psi pressure 1.2 LPM @ 0psi pressure 0.4 LPM @ 0psi pressure
Capacity	Air 100 psi
Colour	Grey Pantone 429 C
Noise	70 dBA
Test Medium	Water
Frame material	Steel
Low pressure pipework	Stainless steel
High pressure pipework	Stainless steel
Stainless steel engraved panel	✓
Weight	250 kg
L x W x H (mm)	2500 x 700 x 1300

FEATURES & BENEFITS

- Top quality components and design - Low maintenance (photo below)
- Transducer and software - Easy to produce test certificates and data storage (Certificate example below)
- Three pump design - Lean and fast operation
- Easy access panels to the front and rear - Fast and easy maintenance
- Forklift access points - Easy to move and transport
- Testing to EN1829-2 - Meeting stringent safety standards



OPTIONAL EXTRAS

- Impulse Testing - 1.5 x WP - hold for 1 minute, 5 x cycles up to WP and down to zero, 1.5 x WP - hold for 1 minute - Parker Polyflex test procedure
- Bespoke and retrofit test tanks
- Touch screen control
- Bespoke step control and software.



Concept, design and complete!