



PROLANCE FITTINGS

TUBE CLEANING

Tube cleaning application

#					Available end connections - male threads			
	DN	size	bar	psi	NPT	Metric	BSP	UNF
2240D-02V32-TC	3	-02	1100	15,950	1/16-27, 1/8-27	M5, M7	-	-
2240D-025V32-TC	4	-025	1200	17,400	1/16-27, 1/8-27, 1/4-18	M7, M8, M10x1	G 1/8	1/4-28
2248D-025V32-TC	4	-025	1500	21,750	-	M7, M8m M10x1	G 1/8	1/4-28
2240D-03V32-TC	5	-03	1000	14,500	1/16-27, 1/8-27, 1/4-18	M7, M8	G 1/8, G 1/4	3/8-24 UNF
2248D-03V32-TC	5	-03	1400	20,300	-	M7, M8	G 1/8, G1/4	3/8-24 UNF
2240D-04V32-TC	6	-04	1100	15,950	1/8-27, 1/4-18	M10x1	G 1/8, G 1/4	3/8-24 UNF
2248D-05V32-TC	8	-05	1000	14,500	1/4-18, 3/8-18	-	G 1/4, G 3/8	-

Note: Working pressure for NPT fittings is limited to 15,000 psi (103.4 MPa).

APPLICATIONS

The shortest and most compact fitting series ever. Used for heat exchangers, pipe and tube interiors, furnaces and boilers.

FEATURES

- Best routing flexibility in narrow and confined spaces (e.g. heat exchangers, small tubes and tight bends).
- Improved corrosion resistance due to stainless steel ferrule.
- Optimized nozzle mounting.
- Available up to 1,500 bar (21,750 psi) working pressure and up to DN 8 (size -05).



Please Note: We reserve the right to make technical changes without notice.