## **POLYFLEX-LOK**

## PARKER POLYFLEX HOSE CONNECTOR

#### Innovative design

Polyflex-Lok has been developed by Parker Polyflex to meet the requirements of today's water jetting applications. It uses the latest technology to provide a "state of the art" hose safety system. The hose connector as well as the pump / gun connector are now equipped with an improved design, based on the reliable quality of the former generation of Polyflex-Lok. The Polyflex-Lok hose assemblies are now also available without protective cover, and hose types with an additional outer cover for extra abrasion resistance and security are also available.

#### What is it?

Efficient and hassle free assembly — Quick connect and release hose connection system which also provides hose burst protection, while ranging in size from DN 5 (3/16") up to DN 12 (1/2"). One major benefit of the system is that it will only operate when full protection of the user is guaranteed. In addition, the Polyflex-Lok system is compliant with requirements determined in DIN EN 1829-2.

#### **Product features**

- Wide range of hose types available from 1,000 up to 3,200 bar working pressure
- Hose sizes available from DN 5 up to DN 12
- Certified according to DIN EN 1829-2
- · Easy, fast, comfortable and safe system
- Only 2 working parts needed
- Integrated safety system
- No spanners required
- · Incorrect assembly and use impossible
- Safety factor 2.5 times (burst pressure)
- Mechanical safety factor 4 times (hose connection breaking load)
- Same parts can be used to connect different hose series (e.g. DN 3 and DN 5)
- Swivel function when system is not under pressure (rotary joints)

#### Major benefits

- Operator protection guaranteed priceless
- Hose twisting eliminated longer hose life
- Faster assembly / disassembly of hoses more valuable working time
- Less wear on components fewer part replacements necessary
- Less operator fatigue due to easy handling and compact design increases efficiency
- In one word: SAFETY!





Please Note: Variety of fittings in mild steel or stainless steel available, other fittings available on request. We reserve the right to make technical changes without notice.



# POLYFLEX-LOK PARKER POLYFLEX HOSE CONNECTOR

### **AVAILABLE HOSE TYPES**


Size	Hose types
-03	2640D-03VXX
-03	2740D-03VXX
-03	2749D-03VXX
-03	2840D-03VXX

Size	Hose types
-05	2380N-05VXXW
-05	2640D-05VXX
-05	2740D-05VXX
-05	2748D-05VX
-05	2840D-05VXX
-05	2848D-05VXX
-05	2741D-05VXX/XX
-05	2748D-05VXX/X
-05	2749D-05VXX
-05	2841D-05VXX/XX

Size	Hose types
-08	2388N-08VXX
-08	2580N-08VXX
-08	2740D-08VXX
-08	2748D-08VXX
-08	2840D-08VXX
-08	2848D-08VXX

### **COMPONENTS**

Reference	Part Number	Description
1	1TM2X-8-03-HPK	Fitting for DN 5 hoses including caps
1	1TM2X-8-05-HPK	Fitting for DN 8 hoses including caps
1	1TMKY-8-05-HPK	Fitting for DN 8 hoses including caps
1	1TMBL-9-08-HPK	Fitting for DN 12 hoses including caps
1	1TMBS-9-08-HPK	Fitting for DN 12 hoses including caps
2	TFTF-8-8	Hose connector bushing
2	TFTF-8-9	Hose connector bushing
2	TFTF-9-9	Hose connector bushing
3	HPK-HS-8	Hose connector
4	HPK-HSP-8	Pump/gun connector
5	YTTF-6-8	Adaptor M20 x 1.5
5	YTTF-9-8	Adaptor M26 x 1.5
5	YTTF-9-9	Adaptor M26 x 1.5
5	YTTF-10-8	Adaptor M30 x 2
5	YTTF-10-9	Adaptor M30 x 2
5	YTTF-12-8	Adaptor M42 x 2
5	YTTF-12-9	Adaptor M42 x 2-6g
5	Y6TF-6-8	Adaptor 3/4 - 16UNF
5	Y6TF-9-8	Adaptor 1 1/8 - 12UNF
6	TMCAP-8	Сар
6	TMCAP-9	Сар





Please Note: Variety of fittings in mild steel or stainless steel available, other fittings available on request. We reserve the right to make technical changes without notice.