

WORKSHOP PRODUCTION CRIMPER

HEAVY DUTY PRODUCTION



HM 3 H



Technical data

	HM 3 H
Crimp force (kN/Ton)	750 / 75
No grease: 20% less friction	✓
Control	Control C.2 + Touch
SAE R12 / 4SP* 2 Piece	1"
4SH* 2 Piece	3/4"
SAE R15* 2 Piece	3/4"
Industrial	2"
90° Elbows	1 1/2"
Max. Crimp range	70mm
Opening	+35mm
Opening without dies	105mm
Master dies length	100mm
Type of dies	239-xx-0-yy
Speed (seconds) - Close	8,3
Speed (seconds) - Crimp	8,3
Speed (seconds) - Open	13,8
Noise level	53 dBA
Drive	5,5 kW 3 VAC
Oil	50 L
L x W x H (mm)	720 x 600 x 672
Weight	193 kg

* According to the fitting.

Ø Types of die	
263-xx-0-yy	
Ø mm	mm
6,8	50
9	50
10	50
12	65
14	65
16	65
17	65
19	65
20	65
22	65
24	65
26	65
28	80
30	80
31	80
32	80
34	80
36	80
38	80
39	80
40	80
44	80
47	100
50	100
54	100
57	100
62	100

Package

QDS 239 B QDC 239.5



Optional Extras (See page 463)



The best return on Investment since 1972.