

HORIZONTAL PRODUCTION CRIMPER NUT / SWIVEL FITTINGS



KS 6 / KS 8 / KS 10



Technical data

	KS 6	KS 8	KS 10
Crimp range	55mm	139mm	139mm
Speed (seconds) - Close	13.1	7	3.5
Speed (seconds) - Crimp	13.1	7	3.5
Speed (seconds) - Open	30	12	6
Noise level	58 dBA	58 dBA	58 dBA
Control	Control C.2	Control C.2	Control C.2
Pressforce (kN/Ton)	1100 / 10	800 / 80	1800 / 180
Jaw type	PBK 237	PBK 237	PBK 237
Opening	+25mm	+45mm	+45mm
Opening without dies	95mm	190mm	190mm
Drive	5.5 kW	5.5 kW	5.5 kW
Oil	40 L	40 L	40 L
Weight	470 kg	570 kg	570 kg
L x W x H (mm)	1000 x 1000 x 1700	1000 x 1000 x 1700	1000 x 1000 x 1700

Jaw type	PBK 239	PBK 237
12	3	3
14	3	3
16	4	4
19	4	4
22	4.5	4.5
24	4.5	4.5
26	4.5	4.5
28	4.5	4.5
32	5	5
36	5	5
40	5	5
47	5	5
50	-	5
54	-	5
57	-	5
62	-	5
67	-	5
71	-	5
74	-	5
78	-	5
84	-	5
86	-	5
90	-	5
96	-	5
103	-	5
106	-	5

Standard

CONTROL B
+ Touch



TA (A)
Automatic backstop



Optional Extras (See page 463)



The best return on Investment since 1972.