

WORKSHOP CRIMPERS MEDIUM DUTY PRODUCTION



S3 Ecoline



S3 L Ecoline



S3 L Mobileline



Technical data

	S3 Ecoline	S3 L Ecoline	S3 L Mobileline
Crimp force (kN/Ton)	1200 / 120	1800 / 180	1800 / 180
No grease: 20% less friction	✓	✓	✓
Control	Control A	Control A	Control A
SAE R12 / 4SP* 1 Piece	1 1/2"	1 1/2"	1 1/2"
SAE R15 / 4SH* 2 Piece	1"	1 1/4"	1 1/4"
SAE R12 / 4SP* 2 Piece	1 1/4"	1 1/2"	1 1/2"
Industrial	2"	2"	2"
90° Elbows	1 1/2"	1 1/4"	1 1/4"
Max. Crimp range	70mm	70mm	70mm
Opening	+35mm	+27mm	+27mm
Opening without dies	105mm	97mm	97mm
Master dies length	100mm	110mm	110mm
Types of dies	239-xx-Ø	239-xx-Ø	239-xx-Ø
Speed (seconds) - Close	4,0	2,0	1,5
Speed (seconds) - Crimp	4,0	2,0	0,4
Speed (seconds) - Open	6,5	7,6	5,7
Noise level	69 dBA	69 dBA	69 dBA
Drive	3 kW 3 VAC	3 kW 3 VAC	1,8 kW 1 VAC
Oil	35 L	35 L	4 L
L x W x H (mm)	592 x 545 x 672	600 x 500 x 630	430 x 370 x 440
Weight	150 kg	150 kg	110kg (without power unit)

Options	S3 Ecoline	S3 L Ecoline	S3 L Mobileline
12 / 24 Volt	-	-	✓
1 Phase	✓	✓	-

Ø Types of die

239-xx-Ø-yy	
Ø mm	mm
6,8	50
9	50
10	50
12	65
14	65
16	65
17	65
19	65
20	65
22	65
24	65
26	65
28	80
30	80
31	80
32	80
34	80
36	80
38	80
39	80
40	80
44	80
47	100
50	100
54	100
57	100
62	100

* According to the fitting.

Package

QDS 239 B QDC 239.5



Optional Extras (See page 463)



The best return on Investment since 1972.