

# WORKSHOP CRIMPERS MEDIUM DUTY PRODUCTION



S4 Ecoline



S4 C.2



S4 DC Mobileline



## Technical data

	S4 Ecoline	S4 C.2	S4 DC Mobileline
Crimp force (kN/Ton)	1800 / 180	1800 / 180	1800 / 180
No grease: 20% less friction	✓	✓	✓
Control	Control A	Control C.2 + Touch	Control A
SAE R12 / 4SP* 1 Piece	2"	2"	2"
SAE R15 / 4SH* 2 Piece	1 1/2"	1 1/2"	1 1/2"
SAE R12 / 4SP* 2 Piece	2"	2"	2"
Industrial	2"	2"	2"
90° Elbows	1 1/2"	1 1/2"	1 1/2"
Max. Crimp range	70mm	70mm	70mm
Opening	+35mm	+35mm	+35mm
Opening without dies	105mm	105mm	105mm
Master dies length	100mm	100mm	100mm
Types of dies	239-xx	239-xx	239-xx
Speed (seconds) - Close	2,7	2,7	0,8
Speed (seconds) - Crimp	2,7	2,7	0,8
Speed (seconds) - Open	4,7	4,7	1,3
Noise level	69 dBA	69 dBA	69 dBA
Drive	3 kW 3 VAC	3 kW 3 VAC	1,8 kW 1 VAC
Oil	35 L	35 L	4 L
L x W x H (mm)	592 x 545 x 672	720 x 600 x 672	509 x 430 x 485
Weight	160 kg	203 kg	132 kg

Options	S4 Ecoline	S4 C.2	S4 DC Mobileline
12 / 24 Volt	-	-	✓
1 Phase	✓	✓	-

Ø Types of die	
239-xx-Ø-yy	
Ø mm	mm
6,8	50
9	50
10	50
12	65
14	65
16	65
17	65
19	65
20	65
22	65
24	65
26	65
28	80
30	80
31	80
32	80
34	80
36	80
38	80
39	80
40	80
44	80
47	100
50	100
54	100
57	100
62	100

\* According to the fitting.

## Package

QDS 239 B    QDC 239.5



## Optional Extras (See page 463)



The best return on Investment since 1972.