

HOSE TEST RIGS

ECOLINE TEST RIG WITH DATA LOGGING



AB-TR-1300-DL



Technical data

	AB-TR-1300-DL
Test pressure	150 - 1300 bar
Drive	Intensifier
Air supply (psi)	100
Flow (at zero pressure)	0.33 L / M
Tank dimensions	On request
Tank capacity	33 litres
Test bench dimensions (mm)	230 x 46 x 98
Reservoir capacity (litres)	33
Side panel	Removable for longer hoses
Test outlet	9/16" UNF suitable for 1/4" MP fitting - Adaptors are available
Data logging and software	Full traceability and production of certificates
Paint	Grey Pantone 429C
Weight	150 kg
Noise Level	72 dBA

FEATURES & BENEFITS

- Usable data logging software
- Easy to install and navigate
- Clear certificates - Gives customer confidence and full traceability
- Easy access panels to the front and rear - Fast and easy maintenance



OPTIONAL EXTRAS

- External water supply
- High pressure pump increased flow to 1.15 L/M
- Pre-fill pump to 16 L / M
- Isolation valve to manually isolate the pump from test hose
- 100 Litre tank
- Increased test cabinet to 3800mm long
- Full test compartment Interlock
- Laptop and software set up
- Printer connected and set up with laptop
- Test adapters



Concept, design and complete! See page 561.