

# HOSE TEST RIGS

## WORKSHOP PRODUCTION



P 160 Ecoline



P 160



### Technical data

	P 160 Ecoline	P 160
Test pressure	150 - 1300 bar	150 - 1300 bar
Drive	Intensifier	Intensifier
Flow	1,1 l / min	1,1 l / min
Capacity	7 bar, 20 NI / min	7 bar, 20 NI / min
Tank dimension (mm)	1200 x 600 x 250	1590 x 975 x 370
Test bench dimension (mm)	1400 x 600 x 1200	2210 x 950 x 1325
Reservoir capacity	33 l	100 l
Colour	RAL 5012 Blue	RAL 5012 Blue, RAL 7021 Grey
Weight	120 kg (Empty)	210 kg (Empty)
Noise level	72 dBA	72 dBA
<b>Accessories</b>		
Suction filter	✓	✓
Air preparation unit	✓	✓
Steck-O-Adapter (s-series only)	DN 4/6/8/10/12/ G 1/2" 405.901	DN 4/6/8/10/12/ G 1/2" 405.901
Steck-O-Adapter (s-series only)	R 1/4" / 3/8" / 1/2" / 3/4" G 1/2" 405.902	R 1/4" / 3/8" / 1/2" / 3/4" G 1/2" 405.902
Anti-corrosive additive	EM 10 l	EM 10 l
<b>Options</b>		
Alternative drive only with pre filling pump 405.904 / 405.914	-	0,38 kW, 400V 50Hz 3Ph
High pressure* (Steck-o-system not available)	-	150 - 3000 bar
Low pressure*	-	20 - 1300 bar

\* Only one of the two options possible.

**Standard**  
Speck-O-System



**Optional Extras**  
(See page 494)



Test bed extension



The best return on Investment since 1972.