

UG 32

SWAGING MACHINE

UG 32 Ecoline



UG 32 Mobileline



Technical data

	UG 32 Ecoline	UG 32 Mobileline
Crimp force (kN / Ton)	250	250
Greased machine	✓	✓
Control	Control A	Control A
SAE R 15 / 4SH* 1 piece fitting	2"	2"
4SH* 2 piece fitting	2"	2"
SAE R 15* 2 piece fitting	1 1/2"	1 1/2"
Industrial	3"	3"
90° Elbows	2"	2"
Crimp range	100mm	100mm
Opening	+ 41mm	+ 41mm
Opening without dies	143mm	143mm
Master dies length	110mm	110mm
Type of dies	239- xx / 266	239- xx / 266
Speed (mm/sec) - Close	1.5	1.1
Speed (mm/sec) - Crimp	1.5	0.3
Speed (mm/sec) - Open	8.7	6.5
Noise level	69 dBA	69 dBA
Drive	3 kW	1.8 kW
Oil	35 L	4 L
L x W x H (mm)	600 x 550 x 750	505 x 430 x 490
Weight	190 kg	145 kg
Options		
12 VDC / 24 VDC	-	✓
1 Phase	✓	✓
3 Phase	✓	-

239-xx-0yy 266		
Ø mm	mm	mm
6,8	50	
9	50	
10	50	
12	65	
14	65	
16	65	
17	65	
19	65	
20	65	
22	65	
24	65	
26	65	
28	80	
30	80	
31	80	
32	80	
36	80	
38	80	
39	80	
40	80	
44	80	
47	100	
50	100	
54	100	
57	100	
62	100	110
67		110
71		110
74		110
78		110
84		110
86		110
92		110

* According to the fitting.

Package

QDS 239 B QDC 239.5

