



With the P 320 and P 350, you can perform precision tests of hoses of up to 2 500 mm in length and with pressures up to 1 000 bar. For the P 320, you can choose between automated and manual setup mode with a pressure up to 4 500 bar as an option. Our P 320 and P 350 have an extra-large test chamber that offers you the space you need to meet any challenge.

Pallets with hoses as well as large, heavy hose coils can be easily supplied to the chamber by forklift. Hose samples are connected easily with adapter hose and quick connection to pressure ports. The P 320 also has a hand clamping option.



P 320



P 320



P 320 with UPP



P 320



P 350 with Container



P 350

Technical Data	P 320 	P 350
Test pressure	150 - 1,500 bar / 2,175 - 21,750 psi	150 - 1,000 bar / 2,175 - 14,500 psi
Control	Manual	IPC
Drive	Diaphragm pump + intensifier	Diaphragm pump + intensifier
Flow (effective)	12.5 l/min	12.5 l/min
Tank dimensions closed (L x W x H) mm (inch)	External: 2,270 x 1,420 x 2,525 (63.3" x 49.6" x 83.8") Internal: 1,607 x 1,260 x 2,130 (89.4" x 55.9" x 99.4")	P 350 Container: External: 2,100 x 2,170 x 2,650 mm (76.8" x 76.8" x 86.6") Internal: 1,950 x 1,950 x 2,200 mm (82.7" x 85.4" x 104.3")
Aggregate dimensions	– (integrated)	850 x 1,390 x 810 mm
Reservoir capacity	150 l	P 350 Container: 1,040 l
Colour	RAL 5012 blue/RAL 7021 grey	RAL 5012 blue/RAL 7021 grey/RAL 9002 rey-white
Weight of tank	P 350 Container: 650 kg	P 350 Container: 650 kg
Weight of power unit	–	210 kg
Noise level	75 dBA	75 dBA
Max. hose length	depending on Ø, several meters on coil possible	depending on Ø, several meters on coil possible
Test medium	Water-oil emulsion EM-CO 18kg	Water-oil emulsion EM-CO 18kg
Accessories		
Pressure + return filter	✓	✓
Air preparation unit	✓	✓
Hand clamping	✓ (1 piece)	–
Options		
Second chambers are possible	–	–
IPC	✓	Standard
Low pressure	20 - 1,500 bar / 290 - 21,750 psi	20 - 1,000 bar / 290 - 14,500 psi
High pressure	150 - 4,500 bar / 2,175 - 65,250 psi	–

P 320:**Steck-o Adapter and Screw Connection:**

1 x Steck-O up to 1,500 bar: 416.1101
 1 x Screw connection up to 4,500 bar: 416.1181

P 320:**Fast clamping system:**

1 x Hand clamping up to 1500 bar: 416.1121
 1 x Hand clamping up to 3000 bar: 416.1151

Description



P 320 Laptop (UPP)



P 320 Interior