

# A-JET SEWER JETTING



## Sewer jetting applications

#	Ø		Ø		⌚		🌿		📐		Kg kg/m
	DN	size	mm	inch	bar	psi	bar	psi	mm		
AJ08-YELLOW	12	-08	12.7	1/2	20.6	290	515	7,500	75	0.23	
AJ12-YELLOW	20	-12	19.2	3/4	29.6	290	515	7,500	125	0.42	
AJ16-YELLOW	25	-16	25.3	1	38.0	290	515	7,500	200	0.61	
AJ20-YELLOW	32	-20	31.9	1 1/4	48.5	290	515	7,500	250	1.14	



## APPLICATIONS

For high pressure water jetting and drain cleaning.

## FEATURES

- European made, premium product.
- Abrasion resistant polyurethane cover provides exceptional cut and fungus resistance.
- Fibre reinforced product meaning low weight and high flexibility
- Excellent cover bonding helps prevent hose damage in aggressive applications.

## CONSTRUCTION

**Core tube:** Special PE compound.  
**Pressure reinforcement:** Two braided layers of high tensile synthetic yarn.  
**Cover:** Abrasion and weather resistant TPU compound.  
**Colour:** Yellow (Leader Hose) and Blue (Main Hose).

## TEMPERATURE RANGE

-20°C to 60°C.

## FITTINGS

BSP Male and Swivel Female  
 NPT Male and NPSM Female



**Please Note:** We reserve the right to make technical changes without notice.