


Hex Nipples



| Male Type "M"              |                            |                  | Dimensions, in. (mm) |             |             |             |             | Male Type "M"               |
|----------------------------|----------------------------|------------------|----------------------|-------------|-------------|-------------|-------------|-----------------------------|
| Px-SAE/MS Thread Size, in. | Px-SAE/MS Thread Size, in. | Ordering Number  | L                    | F           | B           | Bx          | E           | Working Pressure psig (bar) |
|                            |                            |                  |                      |             |             |             |             |                             |
| 3/4-16                     | 9/16-18                    | SS-HPN-TM12-TM9  | 1.51 (38.3)          | 0.75 (19.1) | 0.63 (16.0) | 0.50 (12.7) | 0.09 (2.4)  | 30000 (2068)                |
| 3/4-16                     | 3/4-16                     | SS-HPN-TM12      | 1.64 (41.6)          | 0.75 (19.1) | 0.63 (16.0) | 0.63 (16.0) | 0.29 (7.4)  | 30000 (2068)                |
| 7/8-14                     | 9/16-18                    | SS-HPN-TM14-TM9  | 1.71 (43.5)          | 1.00 (25.4) | 0.76 (19.2) | 0.50 (12.7) | 0.09 (2.4)  | 50000 (3447)                |
| 7/8-14                     | 3/4-16                     | SS-HPN-TM14-TM12 | 1.84 (46.8)          | 1.00 (25.4) | 0.76 (19.2) | 0.63 (16.0) | 0.15 (3.8)  | 30000 (2068)                |
| 7/8-14                     | 7/8-14                     | SS-HPN-TM14      | 1.97 (50.0)          | 1.00 (25.4) | 0.76 (19.2) | 0.76 (19.2) | 0.15 (3.8)  | 50000 (3447)                |
| 1-12                       | 9/16-18                    | SS-HPN-TM16-TM9  | 1.60 (40.6)          | 1.00 (25.4) | 0.64 (16.3) | 0.50 (12.7) | 0.09 (2.4)  | 30000 (2068)                |
| 1-12                       | 3/4-16                     | SS-HPN-TM16-TM12 | 1.73 (43.9)          | 1.00 (25.4) | 0.64 (16.3) | 0.63 (16.0) | 0.29 (7.4)  | 30000 (2068)                |
| 1-12                       | 7/8-14                     | SS-HPN-TM16-TM14 | 1.85 (47.1)          | 1.00 (25.4) | 0.64 (16.3) | 0.76 (19.2) | 0.15 (3.8)  | 30000 (2068)                |
| 1-12                       | 1-12                       | SS-HPN-TM16      | 1.74 (44.2)          | 1.00 (25.4) | 0.64 (16.3) | 0.64 (16.3) | 0.39 (10.0) | 30000 (2068)                |
| 1 5/16-12                  | 1-12                       | SS-HPN-TM21-TM16 | 1.86 (47.2)          | 1.37 (34.9) | 0.62 (15.7) | 0.64 (16.3) | 0.39 (10.0) | 20000 (1379)                |
| 1 5/16-12                  | 1 5/16-12                  | SS-HPN-TM21      | 1.83 (46.6)          | 1.37 (34.9) | 0.62 (15.7) | 0.62 (15.7) | 0.69 (17.5) | 20000 (1379)                |

|                                     |
|-------------------------------------|
| Fittings                            |
| Tubing                              |
| Quick Couplings                     |
| Line Filters                        |
| Valves                              |
| Sour Service Products               |
| Subsea Valves                       |
| Tools and Installation Instructions |
| Technical Information               |
| Part Number Crossover Charts        |