







Due to its narrow, innovative construction, high level of user friendliness, and long service life, the SH 7 sets the standard for quality and cost effectiveness. Balanced weight (2" / 77 kg) and compact engineered design make the SH 7 perfect for workshops and on-site service as well as a service or reserve press for quick use. The proven greaseless slide bearing technology with quick-change system reduces maintenance costs, extends service life and increases accuracy.



SH 7












Type of dies		Type of dies	
239-хх-й-уу			265
Ømm	mm	Ø mm	mm
6.8	65	54	100
9	65	57	100
10	65	62	100
12	65	67	100
14	65	71	100
16	65	74	100
17	65		
19	65		
20	65		
22	65		

		NEW
Technical Data	SH 7	SH 7 S
Crimp force (kN/Ton)	2,400/240	3,200/320
No grease: 20% less friction	✓	✓
Control	Control A	Control A
SAE R 15*/4SH 1 piece fitting	2"	2"
4SH* 2 piece fitting	2"	2"
SAE R 15* 2 piece fitting	11/2"	11/2"
Industrial	2"	2"
90° Elbows	11/2"	11/2"
Max. Crimp range (mm/inch)	82 / 3.23	82 / 3.23
Opening (mm/inch)	+24 / +0.94	+24 / +0.94
Opening without dies (mm/inch)	110 / 4.33	110 / 4.33
Master dies length (mm/inch)	90 / 3.54	90 / 3.54
Type of dies	239 - xx/265	239 - xx/265
Speed (mm/sec)		
Close Crimp Open	Manuell 0.42 Manuell	Manuell 0.42 Manuell
Noise level	70 dBA	70 dBA
Drive	0.75 kW 3 VAC	0.75 kW 3 VAC
Oil	2.31	2.31
L x W x H (mm)	430 x 367 x 682	430 x 367 x 682
Options	77 kg	77 kg
Options		
12 VDC/24 VDC	✓	✓
1 Phase	✓	1
Control IPC	-	-

<sup>\*</sup> According to the fitting.

Packages page 28 / Accessories and options page 56





100


100

57

62

 $\mathsf{SH} = \mathsf{Hollow}\ \mathsf{piston}\ \mathsf{press}\ \mathsf{tool}$ 

## **Description**



The micrometer allows you to easily set the crimping dimensions



manually.



The machine is pre-positioned The lightest mobile 2"-service 265.2 Turntable crimper. Also available in 12 VDC/24 VDC.

