


BSP Female

BSP FEMALE, 60° CONE

T-FBSPORX


PART NUMBER	THREAD	HOSE		DIMENSIONS (mm)	
	F	INCH	DN (mm)	CH	A
4T-4FBSPORX	1/4 - 19	1/4	6	19	17.6
6T-4FBSPORX	1/4 - 19	3/8	10	19	17.7
4T-6FBSPORX	3/8 - 19	1/4	6	22	18.7
6T-6FBSPORX	3/8 - 19	3/8	10	22	18.8
8T-6FBSPORX	3/8 - 19	1/2	12	22	19.4
4T-8FBSPORX	1/2 - 14	1/4	6	27	22.5
6T-8FBSPORX	1/2 - 14	3/8	10	27	20.6
8T-8FBSPORX	1/2 - 14	1/2	12	27	21.2
10T-8FBSPORX	1/2 - 14	3/8	10	27	18.2
12T-8FBSPORX	1/2 - 14	3/4	19	27	24
8T-10FBSPORX	5/8 - 14	1/2	12	30	18.8
10T-10FBSPORX	5/8 - 14	5/8	16	30	21.3
8T-12FBSPORX	3/4 - 14	1/2	12	32	25.3
10T-12FBSPORX	3/4 - 14	5/8	16	32	22.8
12T-12FBSPORX	3/4 - 14	3/4	19	32	22.8
16T-12FBSPORX	3/4 - 14	1	25	32	27.5
12T-16FBSPORX	1 - 11	3/4	19	38	27
16T-16FBSPORX	1 - 11	1	25	38	25



BSP FEMALE 45° ELBOW, 60° CONE

T-FBSPORX

PART NUMBER	THREAD	HOSE		DIMENSIONS		
	F	INCH	DN (mm)	CH	A	B
4T-4FBSPORX45	1/4 - 19	1/4	6	19	41	16
4T-6FBSPORX45	3/8 - 19	1/4	6	22	43	18
6T-6FBSPORX45	3/8 - 19	3/8	10	22	57	18
6T-8FBSPORX45	1/2 - 14	3/8	10	27	60	21
8T-8FBSPORX45	1/2 - 14	1/2	12	27	65	22
10T-10FBSPORX45	5/8 - 14	5/8	16	30	77	25
12T-12FBSPORX45	3/4 - 15	3/4	19	32	82	26
16T-16FBSPORX45	1 - 11	1	25	38	111	31



BSP FEMALE 90° ELBOW COMPACT, 60° CONE

T-FBSPORXBL

PART NUMBER	THREAD	HOSE		DIMENSIONS		
	F	INCH	DN (mm)	CH	A	B
4T-4FBSPORX90BL	1/4 - 19	1/4	6	19	21	23
6T-6FBSPORX90BL	3/8 - 19	3/8	10	22	22	24
8T-8FBSPORX90BL	1/2 - 14	1/2	12	27	24	27
12T-12FBSPORX90BL	3/4 - 14	3/4	19	32	32	35
16T-16FBSPORX90BL	1 - 11	1	25	38	34	40

