EXTREMEFLEX VERSIFLO 150

WATER SUCTION & DELIVERY



Product specifications

#	O		,O				Kg	Length
	inch	mm	mm	bar	psi	mm	kg/m	m
20893098	1	25.4	35.5	10	150	25.4	0.47	30.48
20893099	1 1/4	31.8	41.1	10	150	32	0.54	30.48
20893100	1 1/2	38.1	47.4	10	150	37.1	0.63	30.48
20893101	2	50.8	60.1	10	150	50.8	0.82	30.48
20893102	2 1/2	63.5	75.1	10	150	63.5	1.27	30.48
20893103	3	76.2	87.8	10	150	76.2	1.50	30.48
20893104	4	101.6	114.5	10	150	101.6	2.22	30.48

APPLICATIONS

General purpose water suction and delivery hose, suitable for use in Agricultural applications. Users will see large benefits in handling this hose, especially flexibility and force to bend properties, when comparing to a standard smooth cover hose. Hose manufactured in Canada.

FEATURES

- Ease of handling.
- Very flexible, extremeflex family of products.

CONSTRUCTION

Core tube: Black EPDM.

Pressure reinforcement: Spiral-plied fabrics and double helix wires.

Cover: Corrugated Black EPDM.

TEMPERATURE RANGE

-40°C to 93°C.

Ontinental ★ ContiTech

Please Note: We reserve the right to make technical changes without notice.

