

EFG6K

SAE 100R15



Hydraulic applications

#									
	inch	mm	mm	bar	psi	bar	psi	mm	
6EFG6K	1/4	6	20.3	414	6,000	1655	24,000	64	
8EFG8K	1/2	8	24.1	414	6,000	1655	24,000	89	
10EFG6K	5/8	10	27.7	414	6,000	1655	24,000	102	
12EFG6K	3/4	19	31.5	414	6,000	1655	24,000	119	
16EFG6K	1	25	38.9	414	6,000	1655	24,000	152	
20EFG6K	1 1/4	31	50.0	414	6,000	1655	24,000	208	
20EFG6K	1 1/4	38	50.0	414	6,000	1655	24,000	254	
24EFG6K	1 1/2	51	57.4	414	6,000	1655	24,000	635	
32EFG6K	2	51	71.1	414	6,000	1655	24,000	635	

APPLICATIONS

EFG6K is designed to meet or exceed all requirements of SAE 100R15 specifications.

FEATURES

- Extremely flexible
- Superior flex impulse performance: tested to 1,000,000 impulse cycles at 50% of SAE 100R15 bend radii

CONSTRUCTION

Core tube:

Black, oil resistant, synthetic rubber (Nitrile - Type C)

Pressure reinforcement:

Four (six for -20, -24, and -32) alternating layers of spiraled, high tensile steel.

Cover:

Polychloroprene (Neoprene) - Type A

TEMPERATURE RANGE

-40°C to 121°C.

Please Note: We reserve the right to make technical changes without notice.