

EM 6 | EM 8

UNIFLEX hose cutting machines have been a synonym for the highest precision and robustness for many decades. The solid and compact tools distinguish themselves by their safe and high-quality cutting function. A distinct property is the positioning of the extraordinarily sharp cutting blades close to the powerful motors. This significantly reduces vibration – which is one of the reasons for extreme durability and low maintenance costs.

EM 6 DC



EM 6 M



EM 6 P



EM 6 ECOLINE



EM 8 M



EM 8 P



Technical Data	EM 6 DC	EM 6 M	EM 6 P	EM 6 Ecoline	EM 8 M	EM 8 P
Production: SAE R 13 SAE R 15	-	1 1/4"	1 1/4"	-	1 1/2"	1 1/2"
Workshop: SAE R 13 & SAE R 15	2"	2"	2"	2"	2"	2"
SAE R 12	2"	2"	2 1/2"	2"	2 1/2"	2 1/2"
Industrial	2"	3"	3"	2"	4"	4"
Max. outside	75 mm	95 mm	95 mm	80 mm	120 mm	120 mm
Feed	Manual	Manual	Pneumatic	Manual	Manual	Pneumatic
Noise level	93 dBA	80 dBA	80 dBA	95 dBA	85 dBA	85 dBA
Brake motor	-	✓	✓	-	✓	✓
Suction connection	40 mm	60 mm	60 mm	80 mm	60 mm	60 mm
Drive	3.2 kW : 24 VDC	4.6 kW 3 VAC	4.6 kW 3 VAC	2.4 kW 1 VAC	4.6 kW 3 VAC	4.6 kW 3 VAC
Cutting blade (mm)	TMC 250 x 2 x 40	TMC 350 x 3 x 30	TMC 350 x 3 x 30	TMC 275 x 3 x 25.4	TMC 400 x 4 x 30	TMC 400 x 4 x 30
L x W x H (mm)	740 x 365 x 610	745 x 690 x 430	820 x 785 x 755	700 x 510 x 700	983 x 760 x 875	983 x 760 x 540
Weight	29 kg	75 kg	110 kg	45 kg	122 kg	140 kg
Accessories						
Bench	✓	✓	✓	✓	✓	✓
Suction	✓	✓	✓	✓	✓	✓
UVC 36 Adapter	777.153	777.055	777.055	777.056	777.055	777.055
UVC 50 Adapter	518.7010	518.7012	518.7012	518.7014	518.7012	518.7012
Hose guide (UHG 14)	-	✓	✓	✓	✓	✓
Counter	-	329.1	Standard	-	323.1	323.1



Guide pins ensure straight cuts.



Blades
TM = Plain
TMG = Slotted
TMC = Coated



329.1 (For EM 6 M)
 323.1 (For EM 8)



High-quality cutting blades:
 TMC, TMG and TM.



TMC
 Lasts 7 times longer, cuts twice as fast, generates less smoke, less debris in the hose and less heat.



The best return on Investment since 1972.