






# GTH HYDRAULIC



GTH - RUBBER HYDRAULIC HOSE

## Hydraulic applications

#								
	inch	mm		bar	psi	bar	psi	
3GTH	3/16	5	11.2	34	500	137	2,000	50.8
4GTH	1/4	6	12.7	28	400	110	1,600	63.5
5GTH	5/16	8	14.2	28	400	110	1,600	76.2
8GTH	1/2	12	19.8	28	400	110	1,600	101.6
10GTH	5/8	16	23.1	24	350	96	1,400	127.0
12GTH	3/4	19	26.8	20	300	82	1,200	139.7
16GTH	1	25	28.7	17	250	69	1,000	203.2

## APPLICATIONS

Hydraulic oil lines, heavy-duty transmission oil cooler lines and glycol anti-freeze solutions. Meets or exceeds requirements of SAE 100R6.

## FEATURES

- R6 Hose

## CONSTRUCTION

**Core tube:** Black, oil resistant, synthetic rubber (Nitrile - Type C).  
**Pressure reinforcement:** One fiber braid.  
**Cover:** Black, oil and abrasion resistant, synthetic rubber (Neoprene - Type A).

## TEMPERATURE RANGE

For hydraulic oil lines -40°C to +135°C constant

**Please Note:** We reserve the right to make technical changes without notice.