






LOL HYDRAULIC



Hydraulic applications

| # |  | |  |  | |  | |  |
|--------|---|----|---|---|-----|---|-------|---|
| | inch | mm | | bar | psi | bar | psi | |
| 3LOLA | 3/16 | 5 | 10.4 | 21 | 300 | 83 | 1,200 | 76.2 |
| 4LOLA | 1/4 | 6 | 11.9 | 21 | 300 | 83 | 1,200 | 76.2 |
| 5LOLA | 5/16 | 8 | 14.0 | 21 | 300 | 83 | 1,200 | 76.2 |
| 6LOLA | 3/8 | 10 | 16.0 | 21 | 300 | 83 | 1,200 | 76.2 |
| 8LOLA | 1/2 | 12 | 19.6 | 21 | 300 | 83 | 1,200 | 127.0 |
| 10LOLA | 5/8 | 16 | 23.9 | 21 | 300 | 83 | 1,200 | 152.4 |
| 12LOLA | 3/4 | 19 | 26.9 | 21 | 300 | 83 | 1,200 | 177.8 |

APPLICATIONS

Petroleum-base hydraulic oils, water, glycol antifreeze solutions, engine lubricating oils, and air. Lock-On hose and couplings are NOT recommended for pressure surge applications or critical applications. Do not use for gasoline

FEATURES

- Lock-On Hose

CONSTRUCTION

Core tube: Black, oil resistant, synthetic rubber highly resistant to oil and heat (Nitrile - Type C).
Pressure reinforcement: One fiber braid.
Cover: Oil and abrasion resistant synthetic rubber (Modified Nitrile - Type C2). Available in black Neoprene (LOLA), blue (LOLB), green (LOLG), red (LOLR), yellow (LOLY) and gray (LOLC) colors.

TEMPERATURE RANGE

40°C to +100°C. Air to +71°C only.

Please Note: We reserve the right to make technical changes without notice.