

# P 180

Hose lines that cannot withstand the high pressure for which they are designed can cause serious damage, resulting in high costs - often higher than the price of a test bench. Why take a risk that can be easily avoided?

By testing the quality of your products, you opt for safety. The P 180 workshop test bench allows for the efficient and safe final inspection and testing of hose lines. They are easy to operate and quickly become part of your routine procedures.

## P180



Technical Data	P 180
Test Pressure	150 - 1,300 bar / 2,175 - 18,850 psi
Drive	Oscillating intensifier
Flow	3.5 L / min
Capacity	7.5 bar, 100 NI/min
Tank Dimensions (mm)	2,395 x 825 x 400 (94 x 33 x 15.4)
Test Bench Dimensions (mm)	2,916 x 1,020 x 1,200 (113.6 x 43.7 x 47)
Reservoir Capacity	RAL 5012 Blue, RAL 7021 Gray
Colour	600 kg empty
Noise Level	72 dBA
Test Medium	Water-oil emulsion EM-CO 18kg
Accessories	
Suction Filter	✓
Air Preparation Unit	✓
Steck-O-Adapter (s-series only)	DN 4/6/8/10/12/ G 1/2" 414.902
Steck-O-Adapter (s-series only)	R 1/4" / 3/8" / 1/2" / 3/4" / G 1/2" 405.902
Options	
Alternative Drive Only When Pre Filling Pum 405.904/405.914	-
High Pressure* (Steck-O-System Not available)	150 - 3,000 bar / 2,175 - 43,500 psi
Low Pressure	20 - 1,500 bar / 290 - 21,750 psi
IPC	✓



The best return on Investment since 1972.