

SL3


Next-generation crimper for low pressure hose assemblies. Two-in-one solution with integrated die sets O5 and O15 for DN 03-16. With the SL 3-16 M, UNIFLEX innovates the existing crimper: Two integrated die sets in one tool. No more lost time changing the die. Just change the handle and you are already crimping the other size. No risk of losing dies, no dirty hands, no "time lost". With the built-in handle, you can easily carry it anywhere.

SL 3-32 M and SL 3-75 complete the range with large opening travel up to 3".

SL 3-16 M



Technical Data	SL 3-16 M
Crimp force (kN/Ton)	30/3
Opening travel (mm/inch)	+31.7/+1.24
Industrial	5/8**
Opening without dies (mm/inch)	38.6 / 15.2
Types of dies	150
Master dies length (mm/inch)	10/0.39
L x W x H (mm)	340 x 143 x 780
Weight	20 kg



263


D Types of die	PB263-XX-D Length (mm)
6.8	40
9	75
12	75
14	75
17	75
20	75
24	75
28	75
32	75
36	75
40	75
44	75

SL 3-32 M



Technical Data	SL 3-32 M
Crimp force (kN/Ton)	200/20
Opening travel (mm/inch)	+36.7/+1.44
Industrial	1 1/4* **
Opening without dies (mm/inch)	88 / 3.46
Types of dies	263
Master dies length (mm/inch)	68/2.68
L x W x H (mm)	216 x 165 x 348
Weight	28 kg

Package dies



239

D Types of die	PB293-XX-D Length (mm)
6.8	50
9	50
10	50
12	50
14	60
16	60
17	60
19	60
20	60
20	60
22	60
24	60
26	75
28	75
30	75
31	75
32	75
34	75
36	75
38	75
39	75
40	75
44	75
47	75
50	75
54	75
57	75
62	75

SL 3-75



Technical Data	SL 3-75 M
Crimp force (kN/Ton)	500/50
Opening travel (mm/inch)	+55/+2.16
Industrial	3**
Opening without dies (mm/inch)	115 / 5.52
Types of dies	239
Master dies length (mm/inch)	75/2.95
L x W x H (mm)	420 x 520 x 550
Weight	88 kg



The best return on Investment since 1972.

Package dies