

SC 6 (S 6) | SC 6 S (S 6 S)

With its slim, innovative design, high user-friendliness, versatility and long service life, the SC 6 series with its 4-cylinder technology sets standards for quality and economy. Its very compact design, despite the large opening travel, allows ergonomic working. The long base jaws enable the SC 6 to crimp short 90° fittings up to 2" 4 SP, and the SC 6 S up to 2" R 15. The proven greaseless slide bearing technology reduces maintenance costs, extends service life and increases accuracy. Because the 4-cylinder technology keeps press waste away from the dies, UNIFLEX offers a 3-year warranty for the SC 6 and SC 6 S series.



Technical Data	SC 6 Ecoline	SC 6	SC 6 S Ecoline	SC 6 S
Crimp force (kN/Ton)	2,000 / 200	2,000 / 200	2,800 / 280	2,800 / 280
No grease: 20% less friction	✓	✓	✓	✓
Control	Control A	Control A	Control A	Control A
SAE R 15*/4SH 1 piece fitting	2"	2"	2"	2"
4 SH* 2 piece fitting	2"	2"	2"	2"
SAE R 15* 2 piece fitting	1 1/2"	1 1/2"	2"	2"
Industrial	3"	3"	3"	3"
90° Elbows	2"	2"	2"	2"
Crimp range (mm/inch)	102 / 4.02	102 / 4.02	102 / 4.02	102 / 4.02
Opening (mm/inch)	+45 / +1.77	+45 / +1.77	+45 / +1.77	+45 / +1.77
Opening without dies (mm/inch)	147 / 5.78	147 / 5.78	147 / 5.78	147 / 5.78
Master dies length (mm/inch)	110 / 4.33	110 / 4.33	110 / 4.33	110 / 4.33
Types of dies	239 - xx/266	239 - xx/266	239 - xx/266	239 - xx/266
Speed (mm/sec)				
Close	4.9	9.7	3.0	6
Crimp	2.3	2.2	1.4	1.4
Open	8.2	16	5.3	13.3
Noise Level	69 dBA	67 dBA	69 dBA	67 dBA
Drive	4 kW 3 VAC	4 kW 3 VAC	4 kW 3 VAC	4 kW 3 VAC
Oil	50 L	70 L	50 L	70 L
L X W X H (mm)	700 x 600 x 1360	745 x 600 x 1,360	700 x 600 x 735	745 x 600 x 1,360
Weight	275 kg	375 kg	315 kg	415 kg
Options				
12 VDC/24 VDC	✓	-	✓	-
1 VAC	✓	✓	✓	✓
Control IPC	✓	✓	✓	✓

D Types of die	293-xx-Ø-YY (mm)	266 (mm)
6.8	65	
9	65	
10	65	
12	65	
14	65	
16	65	
17	65	
19	65	
20	65	
22	65	
24	65	
26	65	
28	80	
30	80	
31	80	
32	80	
34	80	
36	80	
38	80	
39	80	
40	80	
44	80	
47	100	
50	100	
54	100	
57	100	
62	100	110
67		110
71		110
74		110
78		110
84		110
86		110
92		110
94		110



The best return on Investment since 1972.

