SH 2 (S 2)

Must workshops and mobile service teams do without the power and reliability of large stationary crimpers? UNIFLEX's ans-wer is a definite "no". Our compact, multi-purpose workshop crimpers prove that the advantages of the legendary slide bearing technology can also be used in light-weight, inexpensive equipment that will fit into almost any vehicle and workshop.

The SH 2 series models offer an optimal force-to-weight ratio of 1" 4 SP at a weight of 29 kg, a large opening stroke up to 22 mm (0.87") and a maximum pressing range up to 63 mm (2.48").

SH 2 M H2

SH 2 M Ecoline

SH2P

SH 2 A

SH 2 LA











Technical Data	SH 2 M H2	SH 2 M Ecoline	SH 2 P	SH 2 A	SH 2 LA
Crimp force (kN/Ton)	900/90	900/90	770/77	900/90	450/45
No grease: 20% less friction	✓	✓	✓	✓	✓
SAE R 12/4SP* 1 piece fitting	11/4"	1 1/4"	11/4"	11/4"	11/4"
SAE R 15/4SH* 2 piece fitting	1"	1"	1"	1"	1"
Industrial	11/4"	11/4"	11/4"	11/4"	11/4"
90° Elbows	1"	1"	1"	1"	1"
Max. Crimp range** (mm/inch)	63 / 2.48	63 / 2.48	63 / 2.48	63 / 2.48	63 / 2.48
Opening (mm/inch)	+22 / +19.06	+22 / +19.06	+22 / +19.06	+22 / +19.06	+22 / +19.06
Master dies length (mm/inch)	75 / 2.95	75 / 2.95	75 / 2.95	75 / 2.95	75 / 2.95
Type of dies	263	263	263	263	263
Speed (mm/sec)					
Close	-	-	0.9	5.8	2.4
Crimp	-	-	0.9	0.6	0.2
Drive	Manual	Manual	Pneumatic	1 VAC	1 VAC
Oil	0.75	0.75	2	1.5	1.5
LXWXH(mm)	500 X 420 X 440	216 x 165 x 348	380 x 400 x 350	450 x 450 x 350	450 x 450 x 450
Weight	32 kg	29 kg	33 kg	41 kg	56 kg

263				
D Types of die	PB263-XX-D Length (mm)			
6.8	40			
9	75			
12	75			
14	75			
17	75			
20	75			
24	75			
28	75			
32	75			
36	75			
40	75			
44	75			
47	75			

Package dies







The best return on Investment since 1972.

