

UVC 50 FSD | UVC 100 FSD

The UNIFLEX hose cutters make clean cuts – but the generation of dust, fumes and odors is inevitable. Therefore, UNIFLEX has developed the UVC 100 suction and filter device for up to three hose cutting machines simultaneously and the UVC 50 for service workshops. A balanced compromise between the volume flow and the negative pressure keeps the air clean during the cutting of hydraulic hose assemblies and protects the operators from fine particles. The multi-step exhaust air purification runs with a spark stop function, cyclone filter technology for the pre-separation of coarse particles, particle filter for dust, HEPA filter for fine particles and carbon filter for odor neutralisation – and all that with a 2-year UNIFLEX manufacturer's warranty.

UVC 50 FSD



UVC 100 FSD



Technical Data	UVC 50 FSD	UVC 100 FSD
Production: SAE R 13 & SAE R 15	700 m ³ /h	1440 m ³ /h
Max. Vacuum	3,250 Pa	4,600 Pa
Main-Filter Surface	5 m ²	10 m ²
Drive Power	3.0 kW	3.0 kW
Intake Voltage	400 Multivoltage	400 Multivoltage
Intake Diameter	80 mm	100 - 160 mm
Dust Collection Container Width	10 L	12 L
Noise Level	69 dBA	69 dBA
L x W x H (mm)	1,180 x 730 x 820	950 x 950 x 2,060
Weight	215 kg	500 kg



The best return on Investment since 1972.