BOLT TENSIONING HOSE

ALL PARKER SYSTEM



Bolt Tensioning Couplings

TEMA Couplings were acquired by Parker Hannifin Corporation in 2007. Tema is a European brand that has typically specialised in High Pressure. Now part of the Parker QRC range, these High Pressure couplings are still manufactured in Europe.

The High Pressure Series of Bolt tensioning couplings are designed to interchange with competitor offerings. These QRCs can be used in all applications where bolting products are used. Whether that be onshore, offshore or even subsea. The couplings are designed to be dry break, to minimise hydraulic fluid contamination. Dust caps are standard to help prolong the life of the fittings. For added safety a locking collar version can also be supplied. The couplings were specially developed for use in industrial machinery, test equipment, rescue equipment, bolt tensioning, torque wrenches etc.

Bolt Tensioning Hose

Hose type 2440D is manufactured by Parker Polyflex division in Germany. This type of hose is the industry standard for bolting applications. The smooth bore and spiralised wire reinforcement helps minimise pressure drop and reduce response times. The hose is very flexible making for easier installations with proven product life. Matched BSP ends are also standard. The 120 degree external BSP cone makes for easy connection to couplings without the need for thread tape or Loctite. Hose assemblies can only be assembled by certified Polyflex companies like Abdex.





All hose assemblies are supplied tested, with certification available as standard.

Combined with Parker Polyflex 2440D series hose, this gives an all Parker Hose and Coupling system for quality and peace of mind.

TECHNICAL INFORMATION



2440D-03 HYDRAULIC APPLICATIONS

#	O				,O						Kg
	DN	size	mm	inch	mm	bar	psi	bar	psi	mm	kg/m
2440D-03V32	5	-03	4.8	3/16	11.5	1500	26,100	4500	65,250	130.0	0.28

HP1500 SERIES - HIGH PRESSURE COUPLINGS

Technical Description

The Tema high pressure coupling was specially developed for use in bolt tensioning equipment. This series is produced in steel. The plug bodies and the sleeves are black galvanised. The coupling can be supplied either with or without additional safety lock.

Advantages

- High flow as a result of optimised valve design.
- Additional plug sealing via polymer valve casing, to guarantee high reliability seals even with second-hand plugs.
- Tema high pressure couplings are supplied with dust caps inclusive.

Features

- Fully interchangeable with CEJN 116 couplings.
- Fully guaranteed match when paired with the Parker Polyflex hose.

Seals

Metal sealing cone threaded adaptors / metal sealing cone adaptors.

Working Pressure

1500 bar.

Working Temperature

 -30° C up to $+100^{\circ}$ C (NBR) depending on the medium. Special seals are available.



www.abdex.com

Abdex Hose & Couplings Ltd

3 Commerce Way, Leighton Buzzard, Bedfordshire LU7 4RW, England. T: +44 (0)1525 377 770. F: sales@ahdex.co.uk

Abdex Industries Pty Ltd - VIC

27 Metcalf Street, Dandenong South, Victoria 3175. T: +61 (3) 9796 3044. F: sales@abdex.com.au

Abdex Industries Pty Ltd - WA

260 Allen Road,
Forrestdale, Western Australia 6112.
T: +61 (8)9418 3044.
E: sales@abdex.com.au

Abdex Industries Pty Ltd – QLD 8/315 Archerfield Road,

Richlands, Queensland 4077.

T: +61 (8)9418 3044.
E: sales@abdex.com.au

Abdex Industries Ptv Lte

1 Sunview Road, Eco-tech@Sunview #07-37, Singapore 627615. T: +65 9753 7478 F: sales@abdex.com.au