

P 260


The P 260 Test Bench with Control IPC are new modular test benches that can be adapted to your needs. They offer the possibility to test with the Steck-o, Hand or Hydraulic quick cone system. You can also install a Euro Pallet inside for the P 260. The controller offers all parameters for a fully automatic test, with visualisation of the pressure and may other features but also connectivity to your server or other machine in line with industry 4.0. or IoT.

P260



Technical Data	P 260
Test Pressure	150 - 1,500 bar / 2,175 - 21,750 psi
Control	IPC
Drive	Oscillating Intensifier
Flow (Effective)	7.5 L/Min
Capacity	7 Bar, 100 NI / Min
Anti Corrosion Additive	Water-oil Emulsion EM-CO 18kg
Tank Dimensions (mm/inch)	2,194 x 890 x 1,100 mm (86" x 35" x 43.3")
Reservoir Capacity	120 L
Loading	250 kg
Weight	900 kg
Noise Level	75 dBA
Capacity Electric	3 VAC
Steck-O	✓
Options	
High Pressure	150 - 4,500 bar / 2,175 - 65,250 psi
Low Pressure	20 - 1,500 bar / 290 - 21,750 psi
Stainless Steel Tank Optional	-
Extended Version On Request L x W x H (mm / inch) Weight	-
VA	✓
Hand Clamping	4 Lines

FEATURES



Axially adjustable quick change system with adjustable rotating head



Sealing tips for hand clamping



Extension of quick system to 2 lines



Barcode Scanner BCR CTR2C-Kit



The best return on Investment since 1972.