

HM 200

As the unrivaled classic in the 1" field, with its narrow, innovative construction, high level of user friendliness, versatility and long service life, the HM 200 sets the unbeatable standard for quality and cost effectiveness. Its compact construction allows for ergono-mic working. The use of different die sets allows pressing of all types of fittings, and the proven greaseless slide bearing technology reduces maintenance costs. The Ecoline model is hydraulically controlled and has a separate tank to save space in workshops.


HM200



HM 200 Ecoline



Technical Data	HM 200	HM 200 Ecoline
Crimp force (kN/Ton)	1,300 / 130	1,300 / 130
No grease: 20% less friction	✓	✓
Control	Control A	Control A
SAE R 12/4SP* 1 piece fitting	1 1/2"	1 1/2"
SAE R 15/4SH* 2 piece fitting	1"	1"
SAE R 12/4SP* 2 piece fitting	1 1/4"	1 1/4"
Industrial	2"	2"
90° Elbows	1 1/2"	1 1/2"
Max. Crimp range (mm/inch)	70 / 2.76	70 / 2.76
Opening (mm/inch)	+30 / +1.18	+30 / +1.18
Opening without dies (mm/inch)	100 / 3.94	100 / 3.94
Master dies length (mm/inch)	75 / 2.95	75 / 2.95
Types of dies	239	239
Speed (mm/sec)		
Close	3.5	3.5
Crimp	3.5	3.5
Open	5.9	5.9
Noise Level	69 dBA	69 dBA
Drive	3 kW 3 VAC	1.8 kW 1 VAC
Oil	35 L	40 L DC4
L X W X H (mm)	800 x 530 x 630	420 x 535 x 520
Weight	140 kg	92kg (without power unit)
Options		
12 VDC/24 VDC	-	✓
1 VAC	✓	2.2 kW
Control IPC	✓	-



D Types of die	PB239-XX-D Length (mm)
6.8	50
9	50
10	50
12	50
14	60
16	60
17	60
19	60
20	60
22	60
24	75
26	75
28	75
30	75
31	75
32	75
34	75
36	75
38	75
39	75
40	75
44	75
47	75
50	75
54	75
57	75
62	75

Package dies



SC =
Press
Tool With
Cylinder



The best return on Investment since 1972.