

# HM 3 H


Due to its narrow and innovative construction, high level of user friendliness, and long service life, the HM 3 H sets new standards for quality and cost effectiveness. With its compact construction, it allows easy, uncomplicated, and “rapid” crimping. The intuitive UNIFLEX Software on the convenient Control C.2 Touch completes the HM 3 H and ensures product quality.

## HM 3 H



Technical Data	HM 3 H
Crimp force (kN/Ton)	750 / 75
No grease: 20% less friction	✓
Control	Control C.2 Touch
SAE R 15*/4SH 1 piece fitting	1"
4 SH* 2 piece fitting	3/4"
SAE R 15* 2 piece fitting	3/4"
Industrial	2"
90° Elbows	1 1/2"
Crimp range (mm/inch)	70 mm / 2.75"
Opening (mm/inch)	+35 / +1.38"
Opening without dies (mm/inch)	105 / 4.13"
Master dies length (mm/inch)	100 / 3.94"
Types of dies	239 - xx/266
Speed (mm/sec)	
Close	8.3
Crimp	8.3
Open	13.8
Noise Level	53 dBA
Drive	5.5 kW 3 VAC
Oil	50 L
L X W X H (mm)	720 x 660 x 672
Weight	193 kg
Options	
Control IPC	✓

### Package dies

 <b>239-XX-Ø-YY</b>	
D Types of die	239-xx-Ø-YY (mm)
6.8	65
9	65
10	65
12	65
14	65
16	65
17	65
19	65
20	65
22	65
24	65
26	65
28	80
30	80
31	80
32	80
34	80
36	80
38	80
39	80
40	80
44	80
47	100
50	100
54	100
57	100
62	100



The best return on Investment since 1972.