






TRUCKVAC - VACUUM HOSE



Product specifications

#							Vacuum			Standard Length
	inch	mm		mm	bar		psi	kg / m		HG
TV-031	1 1/4	31.75	40.6	3.10	45	0.46	29.8	50.8	30.48	
TV-038	1 1/2	38.1	48.2	3.10	45	0.55	29.8	50.8	30.48	
TV-050	2	50.8	60.9	3.10	40	0.74	29.8	63.5	30.48	
TV-063	2 1/2	63.5	76.2	3.10	35	1.30	29.8	63.5	30.48	
TV-076	3	76.2	88.9	3.10	35	1.63	29.8	76.2	30.48	
TV-088	3 1/2	88.9	104.3	3.10	30	2.00	29.8	101.6	30.48	
TV-102	4	101.6	117.6	3.10	30	2.63	29.8	114.3	15.24 / 30.48	
TV-127	5	127	146.3	3.10	30	3.67	28	127	15.24 / 30.48	
TV-152	6	152.4	172.7	3.10	30	4.58	28	233.6	15.24 / 30.48	
TV-203	8	203.2	229.6	3.10	30	8.40	27	381	15.24	
TV-254	10	254	283.9	3.10	28	13.21	25	762	6.096	
TV-304	12	304.8	338	3.10	25	15.52	25	1,016	6.096	

APPLICATIONS

Heavy-duty, abrasion-resistant suction hose for vacuum trucks or handling abrasives, such as the transfer of sand, gravel, cement, fly ash, glass, metals, plastic pellets, fertilisers, rock salts, and slurries.

FEATURES

- Lightweight and flexible.
- Extremely abrasion resistant.
- Antistatic - Static dissipating with no grounding wire.