


2440N

HYDRAULIC & WATER JETTING



Product Specifications

Hydraulic and water jetting applications

#									
	mm	inch	mm	bar	psi	bar	psi	kg/m	mm
2440N-06V30	9.7	3/8	19.4	1400	20,300	3500	50,750	0.73	190.0
2440N-08V30	12.8	1/2	22.5	1400	20,300	3500	50,750	0.95	200.0
2440N-12V30	19.6	3/4	30.0	1000	14,500	2500	36,250	1.39	250.0
2440N-16V30	25.0	1	37.0	900	13,050	2250	32,625	2.00	300.0

Also available with Tough Jacket cover on request.

Applications

Ultra high pressure service for the construction and shipbuilding industries and for general industrial cleaning applications. For use with petroleum or synthetic hydraulic fluids, gas and chemical fluids. Especially suitable for hydraulic bolt tensioning equipment, test rigs, as well as in offshore hydraulic and gas applications.

Features

- Industry standard on ultra high pressure thermoplastic applications
- Light weight and abrasion resistant thermoplastic hose
- Used in hydraulic flying lead bundles

Construction

Core tube:	Polyamide.
Pressure reinforcement:	Four spiral layers of maximum tensile steel wire.
Cover:	Polyamide.
Colour:	Black.

TEMPERATURE RANGE

-10°C up to 100°C.



Please Note: Variety of fittings in mild steel or stainless steel available, other fittings available on request. Abdex reserves the right to make changes to this document.