


PFX10

ULTRA HIGH PRESSURE TUBE CLEANING HOSE



Product Specifications

#										Legacy part number
	mm	inch	mm	bar	psi	bar	psi	kg/m	mm	
PFX10-04-PL	6.4	1/4	11.6	1035	15,000	2588	37,500	0.20	110	2240D-04V32
										2240D-04V32-TC
										2240D-04V62-HT-TC
PFX10-05-PL	8.1	5/16	13.4	1035	15,000	2588	37,500	0.25	120	2248D-05V32
										2248D-05V32-TC
										2248D-05V62-HT-TC

Applications

High pressure service for tube cleaning applications such as heat exchanging in the chemical and oil refining industries. Qualified for water temperatures up to 100°C, making it suitable for hot water systems.

Features

- Compact outside diameter for tight spaces.
- Resistant against hydrolysis, ozone and UV radiation.
- Qualified to 100°C water temperature, suitable for hot water systems.
- PL = Prolance: tough cover qualified with both standard and compact Prolance fitting series.
- In accordance with ISO 23384 and DIN EN 1829-2.
- Design factor greater than 2:1.

Construction

Core tube:	Polyoxymethylene.
Pressure reinforcement:	Two spiral layers of maximum tensile wire.
Cover:	Polyamide, Prolance tough cover.
Colour:	Green.

Temperature Range

-40°C up to +100°C.



Please Note: We reserve the right to make technical changes without notice.