


PFX40

ULTRA HIGH PRESSURE WATER BLASTING HOSE



Product Specifications

#										Legacy part number
	mm	inch	mm	bar	psi	bar	psi	kg/m	mm	
PFX40-03	4.8	3/16	15.1	4000	58,000	8000	116,000	0.64	200	2840D-03V34

ToughJACKET™ version PFX40-03-TJ available on request.

Applications

For very-high pressure lances for the construction and shipbuilding industries or for common industrial cleaning applications. Mainly used for hydrodemolition and removal of accumulated dirt and materials from surfaces such as concrete, asphalt and tanks.

Features

- Meets or exceeds DIN EN 1829-2, which requires hose assemblies to withstand at least 20,000 impulse cycles.
- Available with the quick connect Polyflex Lok system.
- Light weight and flexible.
- ToughJACKET™ double cover available on request for extreme abrasion.
- In accordance with ISO 23384.
- Design factor greater than 2:1.

Construction

Core tube:	Polyoxymethylene.
Pressure reinforcement:	Eight spiral layers of maximum tensile steel wire.
Cover:	Polyamide, alternatively with double cover ToughJACKET™.
Colour:	Red.

Temperature Range

-40°C up to +70°C.



Please Note: We reserve the right to make technical changes without notice.